

View Online at <https://aerobasegroup.com/nsn/5315-00-150-3009>

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Lsubmarine armament and fire control systems; aircraft, intruder a-6e; helicopter, mh-53e; seawolf class ssn; aircraft, eagle f-15; aircraft, tomcat f-14; armanent system; helicopter, advance attack, ah-1w; f4s aircraft

**Grip Length:**

Between 4.300 inches and 4.320 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.890 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Material:**

Steel comp 630 shank or steel comp 632 shank

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0