## NSN 5315-00-150-3058

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-150-3058 **Shank Diameter:** Between 0.2470 inches and 0.2495 inches **Button Handle Diameter:** 1.200 inches **Actuation Method:** Push button **Grip Length:** Between 2.800 inches and 2.820 inches **Actuation Type:** Push Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Shear Strength:** 8200 double pounds per square inch **Shoulder To Head End Distance:** 1.550 inches Pin Attachment Type: Ring **Detent To Tapered End Distance:** 0.380 inches Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Style Designator: Button Test Data Document:** 80205-nas1332 standard (includes industry or association standards, individual manufactureer standards, etc.). **Specification Data:** 80205-nas1334 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A212a0

## NSN 5315-00-150-3058

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6735 spec.