

View Online at <https://aerobasegroup.com/nsn/5315-00-150-3058>

**Shank Diameter:**

Between 0.2470 inches and 0.2495 inches

**Button Handle Diameter:**

1.200 inches

**Actuation Method:**

Push button

**Grip Length:**

Between 2.800 inches and 2.820 inches

**Actuation Type:**

Push

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Shear Strength:**

8200 double pounds per square inch

**Shoulder To Head End Distance:**

1.550 inches

**Pin Attachment Type:**

Ring

**Detent To Tapered End Distance:**

0.380 inches

**Material:**

Steel spring

**Material Specification:**

Qq-w-470 federal specification single material response spring

**Surface Treatment:**

Passivate detent

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response shank

**Style Designator:**

Button

**Test Data Document:**

80205-nas1332 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Specification Data:**

80205-nas1334 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6735 spec.