## NSN 5315-00-150-4021

Headed Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-150-4021

Head Style:FlatDiameter:Between 0.058 inches and 0.062 inchesUnder Head Length:0.390 inchesHardness Rating:53.0 rockwell c and 58.0 rockwell cPin Head Diameter:0.130 inchesSpecial Features:Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depthHeight:0.040 inchesMaterial:Steel comp 440cMaterial Specification:
Diameter:Between 0.058 inches and 0.062 inchesUnder Head Length:0.390 inchesHardness Rating:53.0 rockwell c and 58.0 rockwell cPin Head Diameter:0.130 inchesSpecial Features:Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depthHeight:0.040 inchesMaterial:Steel comp 440c
Between 0.058 inches and 0.062 inches Under Head Length: 0.390 inches Hardness Rating: 53.0 rockwell c and 58.0 rockwell c 53.0 rockwell c
Under Head Length:0.390 inchesHardness Rating:53.0 rockwell c and 58.0 rockwell cPin Head Diameter:0.130 inchesSpecial Features:Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depthHeight:0.040 inchesMaterial:Steel comp 440c
0.390 inches Hardness Rating: 53.0 rockwell c and 58.0 rockwell c Pin Head Diameter: 0.130 inches Special Features: Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depth Height: 0.040 inches Material: Steel comp 440c
Hardness Rating:53.0 rockwell c and 58.0 rockwell cPin Head Diameter:0.130 inchesSpecial Features:Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depthHeight:0.040 inchesMaterial:Steel comp 440c
53.0 rockwell c and 58.0 rockwell c Pin Head Diameter: 0.130 inches Special Features: Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depth Height: 0.040 inches Material: Steel comp 440c
Pin Head Diameter:0.130 inchesSpecial Features:Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depthHeight:0.040 inchesMaterial:Steel comp 440c
0.130 inches Special Features: Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depth Height: 0.040 inches Material: Steel comp 440c
Special Features:Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depthHeight:0.040 inchesMaterial:Steel comp 440c
Slotted drive in head 0.020 in. Min 0.030 in. Maximum width 0.015 in. Min 0.025 in. Maximum depth Height: 0.040 inches Material: Steel comp 440c
Height: 0.040 inches Material: Steel comp 440c
0.040 inches Material: Steel comp 440c
Material: Steel comp 440c
Steel comp 440c
Material Specification:
Ams 5630 assn standard single material response
Style Designator:
Straight
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0