# NSN 5315-00-157-5603

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-157-5603

#### Head Diameter:

Between 0.360 inches and 0.450 inches

#### Shank Diameter:

Between 0.2470 inches and 0.2485 inches

# **Detent Quantity:**

2

#### **Actuation Method:**

Push button

#### Grip Length:

Between 2.800 inches and 2.820 inches

#### **Actuation Type:**

Pull and push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shoulder To Head End Distance:

1.030 inches

### Pin Center To Handle End Distance:

Between 1.200 inches and 1.300 inches

#### Pin Attachment Type:

Link or ring

# Detent To Tapered End Distance:

0.410 inches

# Material:

Steel comp 630 spindle or steel comp 632 spindle

#### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

#### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

#### Style Designator:

L handle

# Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A212a0