# NSN 5315-00-159-3869

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-159-3869

# Head Diameter:

Between 0.360 inches and 0.450 inches

# Shank Diameter:

Between 0.2470 inches and 0.2485 inches

# **Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

# **Detent Quantity:**

2

# **Actuation Method:**

Push button

Grip Length:

Between 2.700 inches and 2.720 inches

# Actuation Type:

Pull and push

# Hardness Rating:

40.0 rockwell c spindle

# Shoulder To Head End Distance:

0.935 inches

# **Pin Attachment Type:**

Hook

# Detent To Tapered End Distance:

Between 0.360 inches and 0.410 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

# **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

# Surface Treatment:

Passivate spindle

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

# Style Designator:

Ring handle

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A212a0