## NSN 5315-00-159-6496

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-159-6496

First End Style:
Chamfered
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.265 inches
Shank Length:
0.189 inches
Shoulder Width Across Flats:
0.438 inches
Shank Diameter:
Between 0.1571 inches and 0.1631 inches
Overall Length:
0.920 inches
Undercut Diameter:
0.125 inches
Undercut Width:
0.060 inches
Second Undercut Width:
0.080 inches
Second Undercut Diameter:
0.230 inches
First End Taper Length:
0.020 inches
Second End Relationship With First End:
Identical
Hardness Rating:
40.0 rockwell c and 43.0 rockwell c
Thread Size:
0.164 inches
Second Shank Diameter:
Between 0.2495 inches and 0.2498 inches
First End Location:
Both ends
First End Taper Angle:
45.0 degrees
Surface Finish:
125.0 microinches large shank
Second Shank Length:

0.265 inches

## NSN 5315-00-159-6496

Headless Shoulder Pin - Page 2 of 2



Material:
Steel comp 416
Material Specification:
Qq-s-764, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Mil-f-14072, e300 military specification single treatment response
Style Designator:
Undercut
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):
Mil-f-14072 spec.