# NSN 5315-00-165-7606

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-165-7606

## Head Diameter:

Between 0.390 inches and 0.505 inches

#### Shank Diameter:

Between 0.3095 inches and 0.3110 inches

## **Detent Quantity:**

2

## **Actuation Method:**

Push button

#### Grip Length:

Between 2.500 inches and 2.520 inches

#### **Actuation Type:**

Pull and push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shoulder To Head End Distance:

1.030 inches

## Pin Center To Handle End Distance:

Between 1.200 inches and 1.300 inches

## Pin Attachment Type:

Link or ring

# Detent To Tapered End Distance:

Between 0.390 inches and 0.440 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

## **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

## Style Designator:

L handle

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A212a0