## NSN 5315-00-175-3771

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-175-3771 First End Style: Square Second End Style: Radius **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.600 inches Width Between Flats: Between 0.375 inches and 0.379 inches First Step Diameter: Between 0.7480 inches and 0.7487 inches First Step Length: 4.100 inches **Second Step Diameter:** Between 0.480 inches and 0.520 inches **Second Step Length:** 1.220 inches **Third Step Diameter:** 0.250 inches Third Step Length: Between 0.710 inches and 0.750 inches **Internal Drive Style:** Socket **Second End Corner Radius:** 0.060 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches First End Location: Threaded end **Criticality Code Justification:** Csym **Surface Finish:** 63.0 microinches shoulder end **Special Features:** Internal drive has 0.250-28 unf-3b thds for depth of 0.910 in.

Material:

Stainless steel

## NSN 5315-00-175-3771

Headless Shoulder Pin - Page 2 of 2



| Material Specification:                         |
|---|
| Ams 5629 assn standard single material response |
| Style Designator:                               |
| Shoulder  |
| Thread Series Designator:                       |
| Unf   |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
| No  |

**Fiig:** A212a0