

View Online at <https://aerobasegroup.com/nsn/5315-00-176-6614>

First End Style:

Chamfered

Head Style:

Flat chamfer

Diameter:

Between 0.3140 inches and 0.3145 inches

Effective Length:

Between 1.2585 inches and 1.2730 inches

Undercut Diameter:

Between 0.240 inches and 0.250 inches

Under Head Length:

Between 2.847 inches and 2.860 inches

Undercut Width:

Between 0.040 inches and 0.050 inches

First Hole Diameter:

Between 0.094 inches and 0.097 inches

Second Hole Diameter:

Between 0.094 inches and 0.097 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.774 inches and 0.804 inches

First End Taper Length:

Between 0.030 inches and 0.050 inches

Hardness Rating:

43.0 rockwell c and 48.0 rockwell c

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

Between 0.490 inches and 0.500 inches

Criticality Code Justification:

Abmz

Height:

Between 0.120 inches and 0.123 inches

Material:

Steel comp 4340

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Mil-p-1623 ty m cl 1 military specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-1623 spec.