

View Online at <https://aerobasegroup.com/nsn/5315-00-176-6614>

**First End Style:**

Chamfered

**Head Style:**

Flat chamfer

**Diameter:**

Between 0.3140 inches and 0.3145 inches

**Effective Length:**

Between 1.2585 inches and 1.2730 inches

**Undercut Diameter:**

Between 0.240 inches and 0.250 inches

**Under Head Length:**

Between 2.847 inches and 2.860 inches

**Undercut Width:**

Between 0.040 inches and 0.050 inches

**First Hole Diameter:**

Between 0.094 inches and 0.097 inches

**Second Hole Diameter:**

Between 0.094 inches and 0.097 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.774 inches and 0.804 inches

**First End Taper Length:**

Between 0.030 inches and 0.050 inches

**Hardness Rating:**

43.0 rockwell c and 48.0 rockwell c

**First End Taper Angle:**

45.0 degrees

**Pin Head Diameter:**

Between 0.490 inches and 0.500 inches

**Criticality Code Justification:**

Abmz

**Height:**

Between 0.120 inches and 0.123 inches

**Material:**

Steel comp 4340

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Mil-p-1623 ty m cl 1 military specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-p-1623 spec.