

View Online at <https://aerobasegroup.com/nsn/5315-00-176-6802>

First End Style:

Chamfered

Head Style:

Dee

Distance From Centerline To Flat:

0.438 inches

Diameter:

Between 0.7495 inches and 0.7500 inches

Effective Length:

4.922 inches

Undercut Diameter:

0.688 inches

Under Head Length:

5.156 inches

Undercut Width:

0.062 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

0.094 inches

Distance From Centerline Of Hole To End Of Pin:

0.187 inches

First End Taper Length:

0.062 inches

Hardness Rating:

58.0 rockwell c and 62.0 rockwell c

First End Taper Angle:

45.0 degrees

Pin Head Diameter:

1.125 inches

Surface Finish:

32.0 microinches outside diameter

Height:

0.375 inches

Material:

Steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Mil-p-16232 ty z cl 2 military specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.