

View Online at <https://aerobasegroup.com/nsn/5315-00-176-6808>

First End Style:

Chamfered

Second End Style:

Chamfered

Shank Length:

Between 0.490 inches and 0.510 inches

Shoulder Diameter:

Between 0.247 inches and 0.249 inches

Shank Diameter:

Between 0.173 inches and 0.175 inches

Overall Length:

Between 0.910 inches and 0.950 inches

First End Taper Length:

Between 0.080 inches and 0.100 inches

Second End Taper Length:

Between 0.010 inches and 0.030 inches

Second End Relationship With First End:

Not identical

Second Shank Diameter:

Between 0.185 inches and 0.187 inches

First End Location:

Long end

First End Taper Angle:

30.0 degrees

Second End Taper Angle:

45.0 degrees

Second Shank Length:

Between 0.260 inches and 0.280 inches

Special Features:

Lg of smaller diameter shoulder 0.080 in. Min 0.100 in. Maximum and lg of larger diameter shoulder 0.060 in. Min 0.080 in. Max

Material:

Steel comp 303

Material Specification:

Qq-s-764, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-f-14072 spec.