

View Online at <https://aerobasegroup.com/nsn/5315-00-176-6808>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Shank Length:**

Between 0.490 inches and 0.510 inches

**Shoulder Diameter:**

Between 0.247 inches and 0.249 inches

**Shank Diameter:**

Between 0.173 inches and 0.175 inches

**Overall Length:**

Between 0.910 inches and 0.950 inches

**First End Taper Length:**

Between 0.080 inches and 0.100 inches

**Second End Taper Length:**

Between 0.010 inches and 0.030 inches

**Second End Relationship With First End:**

Not identical

**Second Shank Diameter:**

Between 0.185 inches and 0.187 inches

**First End Location:**

Long end

**First End Taper Angle:**

30.0 degrees

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

Between 0.260 inches and 0.280 inches

**Special Features:**

Lg of smaller diameter shoulder 0.080 in. Min 0.100 in. Maximum and lg of larger diameter shoulder 0.060 in. Min 0.080 in. Max

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-764, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, e300 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-f-14072 spec.