

View Online at <https://aerobasegroup.com/nsn/5315-00-177-1346>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Thread Length:**

1.000 inches

**Shank Length:**

Between 4.611 inches and 4.621 inches

**Shoulder Diameter:**

Between 0.558 inches and 0.560 inches

**Shank Diameter:**

Between 0.309 inches and 0.311 inches

**Overall Length:**

7.700 inches

**Second End Slot Width:**

Between 0.093 inches and 0.098 inches

**First End Taper Length:**

0.010 inches

**Second End Slot Depth:**

Between 0.051 inches and 0.056 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**First End Location:**

Shank end

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

90.0 microinches shank end

**Special Features:**

0.030 in. W 0.290 in. Diameter undercut located 0.125 in. From shank end

**Material:**

Steel comp 302

**Material Specification:**

Mil-s-7720 military specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-7720 spec.