

View Online at <https://aerobasegroup.com/nsn/5315-00-177-1346>

First End Style:

Chamfered

Second End Style:

Slotted

Thread Class:

3b

Thread Direction:

Right-hand

Thread Length:

1.000 inches

Shank Length:

Between 4.611 inches and 4.621 inches

Shoulder Diameter:

Between 0.558 inches and 0.560 inches

Shank Diameter:

Between 0.309 inches and 0.311 inches

Overall Length:

7.700 inches

Second End Slot Width:

Between 0.093 inches and 0.098 inches

First End Taper Length:

0.010 inches

Second End Slot Depth:

Between 0.051 inches and 0.056 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.375 inches

First End Location:

Shank end

First End Taper Angle:

45.0 degrees

Surface Finish:

90.0 microinches shank end

Special Features:

0.030 in. W 0.290 in. Diameter undercut located 0.125 in. From shank end

Material:

Steel comp 302

Material Specification:

Mil-s-7720 military specification single material response

Surface Treatment:

Passivate

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7720 spec.