

View Online at <https://aerobasegroup.com/nsn/5315-00-177-4088>

Head Diameter:

Between 0.410 inches and 0.470 inches

Shank Diameter:

Between 0.1870 inches and 0.1885 inches

Detent Quantity:

2

Grip Length:

Between 2.200 inches and 2.220 inches

Actuation Type:

Pull

Hardness Rating:

58.0 rockwell c detent and 62.0 rockwell c detent

Shoulder To Head End Distance:

1.125 inches

Pin Center To Handle End Distance:

0.710 inches

Pin Attachment Type:

Link

Detent To Tapered End Distance:

0.260 inches

Material:

Steel comp 1109 shank or steel comp 1110 shank or steel comp 1116 shank or steel comp 1117 shank or steel comp 1118 shank or steel comp 1119 shank or steel comp 1132 shank or steel comp 1137 shank or steel comp 1139 shank or steel comp 1140 shank or steel comp 1141 shank or steel comp 1144 shank or steel comp 1145 shank or steel comp 1146 shank or steel comp 1151 shank or steel comp 1211 shank or steel comp 1212 shank or steel comp 1213 shank or steel comp 1215 shank or steel comp b1111 shank or steel comp b1112 shank or steel comp b1113 shank or steel comp 1214 shank

Material Specification:

Qq-s-637 federal specification all material responses shank

Surface Treatment:

Cadmium shank and chromate shank

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response shank

Style Designator:

Cam lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0