

View Online at <https://aerobasegroup.com/nsn/5315-00-183-6361>

First End Style:

Chamfered

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.275 inches

First Step Diameter:

Between 0.557 inches and 0.559 inches

First Step Length:

1.996 inches

Second Step Diameter:

Between 0.369 inches and 0.371 inches

Second Step Length:

0.549 inches

Third Step Diameter:

0.312 inches

Third Step Length:

0.355 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.186 inches and 0.192 inches

Second Hole Diameter:

Between 0.075 inches and 0.078 inches

Distance From Centerline Of Hole To End Of Pin:

0.700 inches

Center To Center Distance Between Holes:

2.100 inches

First End Taper Length:

0.030 inches

Second End Relationship With First End:

Identical

Thread Size:

0.312 inches

Shear Strength:

220000 single pounds per square inch

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Surface Finish:

125.000 microinches

Material:

Steel

Material Specification:

Nai-1274 fscm 76823 mfr ref single material response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0