

View Online at <https://aerobasegroup.com/nsn/5315-00-195-3606>

**First End Style:**

Chamfered

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.062 inches and 0.065 inches

**Second Hole Diameter:**

Between 0.062 inches and 0.065 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.291 inches

**Center To Center Distance Between Holes:**

1.959 inches

**Pinlength:**

3.625 inches

**Pindiameter:**

Between 0.1870 inches and 0.1872 inches

**First End Taper Length:**

Between 0.015 inches and 0.030 inches

**Second End Relationship With First End:**

Identical

**First End Taper Angle:**

45.0 degrees

**Special Features:**

Third hole 0.062 in. Min 0.065 in. Max diameter located on common vertical center line between 1st and second holes approx 0.490 in. From the second hole

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-764 federal specification single material response

**Special Test Features:**

Special quality control testing

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0