NSN 5315-00-195-3606Headless Straight Pin - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5315-00-195-3606 |
|--|
| First End Style: |
| Chamfered |
| Hole Arrangement Style: |
| Both end drilled |
| First Hole Diameter: |
| Between 0.062 inches and 0.065 inches |
| Second Hole Diameter: |
| Between 0.062 inches and 0.065 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.291 inches |
| Center To Center Distance Between Holes: |
| 1.959 inches |
| Pinlength: |
| 3.625 inches |
| Pindiameter: |
| Between 0.1870 inches and 0.1872 inches |
| First End Taper Length: |
| Between 0.015 inches and 0.030 inches |
| Second End Relationship With First End: |
| Identical |
| First End Taper Angle: |
| 45.0 degrees |
| Special Features: |
| Third hole 0.062 in. Min 0.065 in.Max diameter located on common vertical center line between 1st and secondholes approx 0.490 in. From |
| the second hole |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Qq-s-764 federal specification single material response |
| Special Test Features: |
| Special quality control testing |
| Test Data Document: |
| 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Reference Number Differentiating Characteristics: |
| As differentiated by material which must conform to ships parts control center special quality control provisions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: