

View Online at <https://aerobasegroup.com/nsn/5315-00-198-8116>

First End Style:

Oval

Second End Style:

Oval

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Taper Length:

2.000 inches

Taper Minor Diameter:

Between 0.136 inches and 0.146 inches

Taper Major Diameter:

0.224 inches

Grip Length:

1.875 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.190 inches

Taper:

0.500 per foot in inches

First End Location:

Unthreaded end

First End Outer Radius:

0.015 inches

Second End Outer Radius:

0.015 inches

Material:

Steel comp 4037 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

Material Specification:

An-s-9 federal standard 1st material response or qq-s-689 federal specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6050 military specification 4th material response or mil-s-6098 military specification 5th material response or mil-s-6758 military specification 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.