

View Online at <https://aerobasegroup.com/nsn/5315-00-198-8120>

First End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.422 inches and 0.453 inches

Taper Length:

Between 1.484 inches and 1.516 inches

Taper Minor Diameter:

Between 0.203 inches and 0.207 inches

Taper Major Diameter:

0.259 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.070 inches and 0.080 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.109 inches and 0.141 inches

Grip Length:

Between 1.359 inches and 1.391 inches

Second End Relationship With First End:

Identical

Thread Size:

0.190 inches

Taper:

0.500 per foot in inches

First End Location:

Both ends

Material:

Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

Material Specification:

Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.