NSN 5315-00-200-2277

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-200-2277

First End Style:	
Oval	
Second End Style:	
Square	
Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.438 inches and 0.469 inches	
Taper Length:	
Between 1.234 inches and 1.266 inches	
Taper Minor Diameter:	
Between 0.315 inches and 0.319 inches	
Taper Major Diameter:	
0.367 inches	
Hole Arrangement Style:	
One end drilled	
First Hole Diameter:	
Between 0.076 inches and 0.086 inches	
Distance From Centerline Of Hole To End Of Pin:	
Between 0.109 inches and 0.141 inches	
Grip Length:	
Between 1.109 inches and 1.141 inches	
Second End Relationship With First End:	
Not identical	
Thread Size:	
0.250 inches	
Taper:	
0.500 per foot in inches	
First End Location:	
Oval end	
Material:	
Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130	
Material Specification:	
Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military	
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material	al
response	
Surface Treatment:	
Cadmium	
Surface Treatment Specification:	
Qq-p-416, type 1, cl 3 federal specification single treatment response	
Style Designator:	
Threaded at small end	

NSN 5315-00-200-2277

Threaded Tapered Pin - Page 2 of 2



Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.