## NSN 5315-00-200-2278

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-200-2278

First End Style:
Square
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.438 inches and 0.469 inches
Taper Length:
Between 1.359 inches and 1.391 inches
Taper Minor Diameter:
Between 0.315 inches and 0.319 inches
Taper Major Diameter:
0.375 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.076 inches and 0.086 inches
Distance From Centerline Of Hole To End Of Pin:
Between 0.109 inches and 0.141 inches
Grip Length:
Between 1.234 inches and 1.266 inches
Second End Relationship With First End:
Identical
Thread Size:
0.250 inches
Taper:
0.506 per foot in inches
First End Location:
Threaded end
Material:
Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130
Material Specification:
Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material
response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response

## Style Designator:

Threaded at small end

## **Thread Series Designator:**

Unf

## NSN 5315-00-200-2278

Threaded Tapered Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.

