## NSN 5315-00-200-2279



Threaded Tapered Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-200-2279 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.438 inches and 0.469 inches Taper Length: Between 1.484 inches and 1.516 inches **Taper Minor Diameter:** Between 0.315 inches and 0.319 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.076 inches and 0.086 inches **Distance From Centerline Of Hole To End Of Pin:** Between 0.109 inches and 0.144 inches **Grip Length:** Between 1.359 inches and 1.391 inches **Thread Size:** 0.250 inches Taper: 0.500 per foot in inches Material: Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 **Material Specification:** Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Style Designator:** Threaded at small end **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Fiig:** A212a0

No

**Demilitarization:** 

## NSN 5315-00-200-2279

Threaded Tapered Pin - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.