NSN 5315-00-200-2281

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-200-2281 First End Style: Square Second End Style: Square **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.438 inches and 0.469 inches **Taper Length:** Between 1.797 inches and 1.828 inches **Taper Minor Diameter:** Between 0.503 inches and 0.507 inches **Taper Major Diameter:** 0.390 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: Between 0.076 inches and 0.086 inches **Distance From Centerline Of Hole To End Of Pin:** Between 0.109 inches and 0.141 inches **Grip Length:** Between 1.609 inches and 1.641 inches Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches Taper: 0.500 per foot in inches First End Location: Threaded end Material: Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 **Material Specification:** Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response **Surface Treatment:** Cadmium

Threaded at small end

Style Designator:

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

NSN 5315-00-200-2281

Threaded Tapered Pin - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):

Mil-s-6049 spec.