## NSN 5315-00-200-2281

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-200-2281

First End Style:
Square
Second End Style:
Square
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.438 inches and 0.469 inches
Taper Length:
Between 1.797 inches and 1.828 inches
Taper Minor Diameter:
Between 0.503 inches and 0.507 inches
Taper Major Diameter:
0.390 inches
Hole Arrangement Style:
One end drilled
First Hole Diameter:
Between 0.076 inches and 0.086 inches
Distance From Centerline Of Hole To End Of Pin:
Between 0.109 inches and 0.141 inches
Grip Length:
Between 1.609 inches and 1.641 inches
Second End Relationship With First End:
Not identical
Thread Size:
0.250 inches
Taper:
0.500 per foot in inches
First End Location:
Threaded end
Material:
Steel comp 2330 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130
Material Specification:
Qq-s-689 federal specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material
response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification single treatment response
Style Designator:
Threaded at small end

## NSN 5315-00-200-2281

Threaded Tapered Pin - Page 2 of 2



**Thread Series Designator:** 

Unf

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A212a0

## Mil-std (military Standard):

Mil-s-6049 spec.