## NSN 5315-00-208-1946

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-208-1946 First End Style: Square w/thru hole **Second End Style:** Chamfered w/thru hole **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.440 inches First Step Length: 0.380 inches **Second Step Diameter:** 0.375 inches **Second Step Length:** 0.500 inches Third Step Diameter: Between 0.279 inches and 0.283 inches Third Step Length: Between 0.230 inches and 0.250 inches **Second End Relationship With First End:** Not identical **Thread Size:** 0.375 inches **First End Location:** Tapered end **Second End Taper Angle:** 30.0 degrees First Step Width Across Flats: Between 0.430 inches and 0.446 inches **Special Features:** 0.266 in. Min 0.270 in. Maximum smallest end third step dia Material: Plastic epoxy and glass fiber **Material Specification:** Mil-p-18177 military specification single material response **Style Designator:** Shoulder **Thread Series Designator:** 

Thread Series
Unc
Shelf Life:
N/a

## NSN 5315-00-208-1946

Headless Shoulder Pin - Page 2 of 2



|  | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-18177 spec.