

View Online at <https://aerobasegroup.com/nsn/5315-00-210-0836>

**First End Style:**

Chamfered

**Overall Length:**

Between 1.302 inches and 1.322 inches

**Diameter:**

Between 0.3740 inches and 0.3745 inches

**Effective Length:**

Between 1.125 inches and 1.130 inches

**Undercut Diameter:**

Between 0.350 inches and 0.354 inches

**Undercut Width:**

Between 0.028 inches and 0.031 inches

**Second Undercut Width:**

Between 0.028 inches and 0.031 inches

**First End Taper Length:**

Between 0.021 inches and 0.041 inches

**Features Provided:**

Casehardened

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

40.0 rockwell c and 45.0 rockwell c

**First End Location:**

Both ends

**First End Taper Angle:**

Between 40.0 degrees and 50.0 degrees

**Surface Finish:**

16.0 microinches outside diameter

**Material:**

Steel comp 1040 or steel comp 1041 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045

**Material Specification:**

Sae assn standard all material responses

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Mil-p-16232, type 1 military specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-p-16232 spec.