## NSN 5315-00-211-7660

Headed Shoulder Pin - Page 1 of 1

Mil-std (military Standard):

Mil-p-16232 spec.



View Online at https://aerobasegroup.com/nsn/5315-00-211-7660 First End Style: Round First Step Diameter: Between 0.499 inches and 0.501 inches **Second Step Diameter:** Between 0.277 inches and 0.279 inches Second Step Length: Between 1.343 inches and 1.353 inches Hardness Rating: 40.0 rockwell c and 45.0 rockwell c First End Outer Radius: Between 0.140 inches and 0.160 inches **Surface Finish:** 125.0 microinches Material: Steel comp 4140 **Material Specification:** Astm a322 assn standard single material response or astm a331 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-p-16232 ty m cl 3 military specification single treatment response or mil-p-16232 ty z cl 3 military specification single treatment response **Style Designator:** Shoulder **Test Data Document:** 81349-mil-t-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A212a0