

View Online at <https://aerobasegroup.com/nsn/5315-00-224-9230>

First End Style:

Chamfered

Second End Style:

Pointed

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.440 inches

Shank Length:

0.500 inches

Shoulder Width Across Flats:

0.500 inches

Shank Diameter:

Between 0.249 inches and 0.250 inches

Overall Length:

1.425 inches

First End Taper Length:

0.050 inches

Second End Taper Length:

0.185 inches

Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

Second Shank Diameter:

Between 0.249 inches and 0.250 inches

First End Location:

Short shank end

First End Taper Angle:

45.0 degrees

Surface Finish:

125.000 microinches

Second End Taper Angle:

62.0 degrees

Second Shank Length:

0.835 inches

Special Features:

0.060 in. Spherical radius on pointed end

Material:

Steel comp 303

Material Specification:

Qq-s-764 cond b federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.