

View Online at <https://aerobasegroup.com/nsn/5315-00-224-9423>

**First End Style:**

Square

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.422 inches and 0.454 inches

**Taper Length:**

Between 1.734 inches and 1.766 inches

**Taper Minor Diameter:**

Between 0.253 inches and 0.257 inches

**Taper Major Diameter:**

0.330 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.070 inches and 0.080 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.109 inches and 0.141 inches

**Grip Length:**

Between 1.609 inches and 1.641 inches

**Second End Relationship With First End:**

Identical

**Thread Size:**

0.190 inches

**Taper:**

0.500 per foot in inches

**First End Location:**

Both ends

**Material:**

Steel comp 4037 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

**Material Specification:**

An-s-9 federal standard 1st material response or qq-s-689 federal specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6050 military specification 4th material response or mil-s-6098 military specification 5th material response or mil-s-6758 military specification 5th material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification single treatment response

**Style Designator:**

Threaded at small end

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6049 spec.