NSN 5315-00-234-1846

Cotter Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-234-1846

Diameter:
Between 0.146 inches and 0.150 inches
Underloop Length:
Between 2.375 inches and 2.625 inches
End Application:
$W/s: trailer, \ semi \ (m747) (het); \ truck, \ dump, \ 5-ton, \ 6x6 \ (m929, \ m930); \ engine, aircraft \ tf33-pw-102 \ (c-135e, \ ec-135h/k/p); \ truck, \ tractor, \ truck, \ tru$
5-ton (m818, m931); truck, wrecker, 5-ton (m936); truck, cargo, dropside, xlwb, 5-ton, 6x6 (m814, m927, m928); engine, aircraft
tf-34; truck, cargo, dropside, 5-ton, 6x6 (m1831a1, m-923, m-925); engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); engine, aircraft,
tf-33-p-7)c-141a/b)
Point Type:
Extended prong square cut
Material:
Steel
Material Specification:
Astm e30 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Style Designator:
Standard
Shelf Life:
N/a
Unit Of Measure:

Domilitarization

Demilitarization:

No

Fiig:

A212a0