

View Online at <https://aerobasegroup.com/nsn/5315-00-234-1863>

**Diameter:**

Between 0.086 inches and 0.090 inches

**Underloop Length:**

Between 0.688 inches and 0.875 inches

**End Application:**

W/s: stream (std. Tensioned replenishment at sea method); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); shipboard material handling equipment (mhe); trainer, b-1b aircraft; aircraft, airlifter c-17a; aircraft, eagle f-15; aircraft, hx unique; support equipment, b-1 aircraft; airborne mobile dir air spt ctl (2id), (02m jul83) (an/uyq-3a); fire pumps; hemtt family (heavy expanded mobility tactical trucks)

**Point Type:**

Extended prong mitre end

**Hardness Rating:**

60.0 rockwell superficial 15-n and 70.0 rockwell superficial 15-n

**Material:**

Steel comp 302 or steel comp 304

**Material Specification:**

Astm a493 assn standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response

**Style Designator:**

Standard

**Departure From Cited Designator:**

As modified by point style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0