

View Online at <https://aerobasegroup.com/nsn/5315-00-234-1863>

Diameter:

Between 0.086 inches and 0.090 inches

Underloop Length:

Between 0.688 inches and 0.875 inches

End Application:

W/s: stream (std. Tensioned replenishment at sea method); engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); shipboard material handling equipment (mhe); trainer, b-1b aircraft; aircraft, airlifter c-17a; aircraft, eagle f-15; aircraft, hx unique; support equipment, b-1 aircraft; airborne mobile dir air spt ctl (2id), (02m jul83) (an/uyq-3a); fire pumps; hemtt family (heavy expanded mobility tactical trucks)

Point Type:

Extended prong mitre end

Hardness Rating:

60.0 rockwell superficial 15-n and 70.0 rockwell superficial 15-n

Material:

Steel comp 302 or steel comp 304

Material Specification:

Astm a493 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a380 assn standard single treatment response

Style Designator:

Standard

Departure From Cited Designator:

As modified by point style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0