

View Online at <https://aerobasegroup.com/nsn/5315-00-235-3536>

First End Style:

Slotted

Second End Style:

Square

Thread Class:

2a

Thread Direction:

Right-hand

Shank Length:

Between 0.833 inches and 0.873 inches

Shoulder Diameter:

Between 0.556 inches and 0.560 inches

Shank Diameter:

Between 0.478 inches and 0.492 inches

Overall Length:

Between 4.400 inches and 4.420 inches

Internal Drive Style:

Slot

First End Slot Width:

Between 0.100 inches and 0.140 inches

First End Slot Depth:

Between 0.070 inches and 0.110 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

40.0 rockwell c and 45.0 rockwell c

Thread Size:

0.375 inches

First End Location:

Threaded end

Surface Finish:

250.0 microinches shoulder end

Special Features:

Secondary step on shank end 0.540 in. Min 0.554 in. Maximum diameter 0.308 in. Min 0.318 in. Maximum width thread relief to root dia

Material:

Steel comp 4340

Material Specification:

Qq-s-624 federal specification single material response

Surface Treatment:

Phosphate manganese or phosphate zinc

Surface Treatment Specification:

Mil-p-16232 type m, class 1 military specification 1st treatment response or mil-p-16232, type z, class 3 military specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.