

View Online at <https://aerobasegroup.com/nsn/5315-00-235-4750>

First End Style:

Chamfered

Second End Style:

Slotted

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.562 inches

Internal Drive Style:

Slot

Pinlength:

8.531 inches

Pindiameter:

Between 0.4350 inches and 0.4360 inches

Second End Slot Width:

0.062 inches

First End Taper Length:

0.016 inches

Second End Slot Depth:

0.094 inches

Thready Qty Per Inch (tpi):

20

Second End Relationship With First End:

Not identical

Thread Size:

0.437 inches

First End Location:

Shank end

First End Taper Angle:

45.0 degrees

Pin Grip Length:

7.969 inches

Special Features:

Groove 0.384 in. To 0.392 in. Diameter by 0.048 in. To 0.051 in. W spaced 1-21/32 in. From thd end

Material:

Steel comp 1144

Material Specification:

Qq-s-637, cond cd and sr federal specification single material response

Surface Treatment:

Tin

Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0

Mil-std (military Standard):

Mil-t-10727 spec.