

View Online at <https://aerobasegroup.com/nsn/5315-00-235-4750>

**First End Style:**

Chamfered

**Second End Style:**

Slotted

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.562 inches

**Internal Drive Style:**

Slot

**Pinlength:**

8.531 inches

**Pindiameter:**

Between 0.4350 inches and 0.4360 inches

**Second End Slot Width:**

0.062 inches

**First End Taper Length:**

0.016 inches

**Second End Slot Depth:**

0.094 inches

**Thready Qty Per Inch (tpi):**

20

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.437 inches

**First End Location:**

Shank end

**First End Taper Angle:**

45.0 degrees

**Pin Grip Length:**

7.969 inches

**Special Features:**

Groove 0.384 in. To 0.392 in. Diameter by 0.048 in. To 0.051 in. W spaced 1-21/32 in. From thd end

**Material:**

Steel comp 1144

**Material Specification:**

Qq-s-637, cond cd and sr federal specification single material response

**Surface Treatment:**

Tin

**Surface Treatment Specification:**

Mil-t-10727, type 1 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-t-10727 spec.