## NSN 5315-00-235-4750

Threaded Straight Pin - Page 1 of 2

Tin



View Online at https://aerobasegroup.com/nsn/5315-00-235-4750

First End Style:
Chamfered
Second End Style:
Slotted
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.562 inches
Internal Drive Style:
Slot
Pinlength:
8.531 inches
Pindiameter:
Between 0.4350 inches and 0.4360 inches
Second End Slot Width:
0.062 inches
First End Taper Length:
0.016 inches
Second End Slot Depth:
0.094 inches
Thready Qty Per Inch (tpi):
20
Second End Relationship With First End:
Not identical
Thread Size:
0.437 inches
First End Location:
Shank end
First End Taper Angle:
45.0 degrees
Pin Grip Length:
7.969 inches
Special Features:
Groove 0.384 in. To 0.392 in. Diameter by 0.048 in. To 0.051 in. W spaced 1-21/32 in. From thd end
Material:
Steel comp 1144
Material Specification:
Qq-s-637, cond cd and sr federal specification single material response
Surface Treatment:

## NSN 5315-00-235-4750

Threaded Straight Pin - Page 2 of 2



Surface Treatment Specification:

Mil-t-10727, type 1 military specification single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-10727 spec.