

View Online at <https://aerobasegroup.com/nsn/5315-00-235-4878>

First End Style:

Chamfered

Shank Length:

2.031 inches

Shoulder Diameter:

0.750 inches

Shank Diameter:

Between 0.6220 inches and 0.6235 inches

Overall Length:

11.094 inches

Hole Arrangement Style:

Both end drilled

First Hole Diameter:

Between 0.187 inches and 0.192 inches

Second Hole Diameter:

Between 0.187 inches and 0.192 inches

Distance From Centerline Of Hole To End Of Pin:

1.594 inches

Center To Center Distance Between Holes:

Between 7.896 inches and 7.916 inches

First End Taper Length:

0.031 inches

Second End Relationship With First End:

Identical

First End Location:

Both ends

First End Taper Angle:

45.0 degrees

Surface Finish:

32.0 microinches shank end

Special Features:

Shoulder primed per tt-p-659 enamel white per tt-e-489; 29.0 degrees min 31.0 degrees maximum angle between centerlines of holes

Material:

Steel

Material Specification:

66, 1010 to 1025 federal standard single material response

Surface Treatment:

Phosphate manganese

Surface Treatment Specification:

Mil-p-16232, cl 2 military specification single treatment response

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-p-16232 spec.