

View Online at <https://aerobasegroup.com/nsn/5315-00-235-4878>

**First End Style:**

Chamfered

**Shank Length:**

2.031 inches

**Shoulder Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.6220 inches and 0.6235 inches

**Overall Length:**

11.094 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

Between 0.187 inches and 0.192 inches

**Second Hole Diameter:**

Between 0.187 inches and 0.192 inches

**Distance From Centerline Of Hole To End Of Pin:**

1.594 inches

**Center To Center Distance Between Holes:**

Between 7.896 inches and 7.916 inches

**First End Taper Length:**

0.031 inches

**Second End Relationship With First End:**

Identical

**First End Location:**

Both ends

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

32.0 microinches shank end

**Special Features:**

Shoulder primed per tt-p-659 enamel white per tt-e-489; 29.0 degrees min 31.0 degrees maximum angle between centerlines of holes

**Material:**

Steel

**Material Specification:**

66, 1010 to 1025 federal standard single material response

**Surface Treatment:**

Phosphate manganese

**Surface Treatment Specification:**

Mil-p-16232, cl 2 military specification single treatment response

**Style Designator:**

Shoulder

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-p-16232 spec.