NSN 5315-00-242-4535

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-242-4535

| First End Style: | |
|---|--|
| Chamfered | |
| Shank Length: | |
| Between 0.400 inches and 0.420 inches | |
| Shoulder Diameter: | |
| 0.375 inches | |
| Shank Diameter: | |
| Between 0.240 inches and 0.245 inches | |
| Overall Length: | |
| Between 0.930 inches and 0.960 inches | |
| First End Taper Length: | |
| Between 0.010 inches and 0.030 inches | |
| Second End Taper Length: | |
| Between 0.040 inches and 0.060 inches | |
| Second End Relationship With First End: | |
| Identical | |
| Hardness Rating: | |
| 40.0 rockwell c and 45.0 rockwell c | |
| Second Shank Diameter: | |
| Between 0.2505 inches and 0.2510 inches | |
| First End Location: | |
| Short shank end | |
| First End Taper Angle: | |
| 45.0 degrees | |
| Second End Taper Angle: | |
| Between 29.5 degrees and 30.5 degrees | |
| Second Shank Length: | |
| Between 0.240 inches and 0.330 inches | |
| Material: | |
| Steel comp 4140 | |
| Material Specification: | |
| Aisi assn standard single material response | |
| Surface Treatment: | |
| Cadmium and chromate | |
| Surface Treatment Specification: | |
| Qq-p-416, type 2, class 1 federal specification single treatment response | |
| Style Designator: | |
| Shoulder | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

--

NSN 5315-00-242-4535

Headless Shoulder Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0