NSN 5315-00-242-9191

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-242-9191

| First End Style: |
|--|
| Chamfered |
| Second End Style: |
| Round |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.625 inches |
| Shank Length: |
| 0.814 inches |
| Shoulder Diameter: |
| 0.828 inches |
| Shank Diameter: |
| Between 0.561 inches and 0.562 inches |
| Overall Length: |
| 1.750 inches |
| First End Taper Length: |
| 0.047 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.562 inches |
| Second Shank Diameter: |
| Between 0.5635 inches and 0.5645 inches |
| First End Location: |
| Threaded end |
| First End Taper Angle: |
| 45.0 degrees |
| Surface Finish: |
| 63.0 microinches |
| Second End Outer Radius: |
| 0.281 inches |
| Second Shank Length: |
| 0.843 inches |
| Special Features: |
| Thread relief 0.170 in. W, 0.475 in. Dia |
| Material: |
| Steel comp 4140 |
| Material Specification: |
| Mil-s-5626 cond c4 military specification single material response |

NSN 5315-00-242-9191

Headless Shoulder Pin - Page 2 of 2



| Surface Treatment: |
|---------------------------|
| Chromium |
| Style Designator: |
| Shoulder |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |

Mil-std (military Standard):

Mil-s-5626 spec.