## NSN 5315-00-245-3517

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-245-3517 First End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.620 inches **Shank Length:** 0.680 inches **Shoulder Diameter:** 0.375 inches **Shank Diameter:** Between 0.245 inches and 0.250 inches **Overall Length:** Between 1.984 inches and 2.016 inches **Internal Drive Style:** Slot First End Taper Length: 0.020 inches **Second End Relationship With First End:** Identical **Thread Size:** 0.375 inches **Second Shank Diameter:** Between 0.245 inches and 0.250 inches **First End Location:** Both ends First End Taper Angle: 45.0 degrees **Second Shank Length:** 0.700 inches **Special Features:** Threaded shoulder Material: Steel comp 303 **Material Specification:** Astm a-582 cond1 assn standard single material response **Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Mil-f-14072, e300 military specification single treatment response

## NSN 5315-00-245-3517

Headless Shoulder Pin - Page 2 of 2



Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

Mil-std (military Standard):

Style Designator:

Mil-f-14072 spec.