

View Online at <https://aerobasegroup.com/nsn/5315-00-264-0121>

**First End Style:**

Chamfered

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.250 inches

**Shank Length:**

Between 0.279 inches and 0.389 inches

**Shoulder Width Across Flats:**

Between 0.111 inches and 0.113 inches

**Shank Diameter:**

Between 0.091 inches and 0.095 inches

**Overall Length:**

0.700 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

0.032 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.093 inches

**First End Taper Length:**

Between 0.020 inches and 0.059 inches

**Thready Qty Per Inch (tpi):**

40

**Second End Relationship With First End:**

Identical

**Thread Size:**

0.112 inches

**Second Shank Diameter:**

0.112 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

Between 45.0 degrees and 60.0 degrees

**Second Shank Length:**

Between 0.279 inches and 0.389 inches

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Gold

**Surface Treatment Specification:**

Mil-g-45204 type 2 class 1 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0

**Mil-std (military Standard):**

Mil-g-45204 spec.