

NSN 5315-00-264-0121 Headless Shoulder Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-264-0121 First End Style: Chamfered **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Shank Length:** Between 0.279 inches and 0.389 inches **Shoulder Width Across Flats:** Between 0.111 inches and 0.113 inches **Shank Diameter:** Between 0.091 inches and 0.095 inches **Overall Length:** 0.700 inches **Hole Arrangement Style:** One end drilled First Hole Diameter: 0.032 inches **Distance From Centerline Of Hole To End Of Pin:** 0.093 inches First End Taper Length: Between 0.020 inches and 0.059 inches Thready Qty Per Inch (tpi): 40 Second End Relationship With First End: Identical **Thread Size:**

0.112 inches

Second Shank Diameter:

0.112 inches

First End Location:

Threaded end

First End Taper Angle:

Between 45.0 degrees and 60.0 degrees

Second Shank Length:

Between 0.279 inches and 0.389 inches

Material:

Steel comp 303

Material Specification:

Astm a582 assn standard single material response

NSN 5315-00-264-0121

Headless Shoulder Pin - Page 2 of 2

Mil-g-45204 spec.



Surface Treatment:
Gold
Surface Treatment Specification:
Mil-g-45204 type 2 class 1 military specification single treatment response
Style Designator:
Shoulder
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0
Mil-std (military Standard):