NSN 5315-00-265-9895

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-265-9895

| First End Style: | |
|---|---|
| Oval | |
| Second End Style: | |
| Square | |
| Thread Class: | |
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| Between 0.438 inches and 0.453 inches | |
| Taper Length: | |
| Any acceptable | |
| Taper Minor Diameter: | |
| Between 0.315 inches and 0.319 inches | |
| Taper Major Diameter: | |
| Any acceptable | |
| Grip Length: | |
| Between 1.234 inches and 1.266 inches | |
| Thready Qty Per Inch (tpi): | |
| 28 | |
| Second End Relationship With First End: | |
| Not identical | |
| Thread Size: | |
| 0.250 inches | |
| Taper: | |
| 0.500 per foot in inches | |
| First End Location: | |
| Oval end | |
| First End Outer Radius: | |
| Any acceptable | |
| Material: | |
| Steel or steel comp 8740 or steel comp 8630 or steel | comp 8735 or steel comp 4130 |
| Material Specification: | |
| Qq-s-681 federal specification 1st material response of | r mil-s-6049 military specification 2nd material response or mil-s-6050 military |
| specification 3rd material response or mil-s-6098 milita | ary specification 4th material response or mil-s-6758 military specification 5th material |
| response | |
| Surface Treatment: | |
| Cadmium | |
| Surface Treatment Specification: | |
| Qq-p-416, type 1, cl 3 federal specification single treat | ment response |
| Style Designator: | |
| Threaded at small end | |
| | |

Thread Series Designator:

Unf

NSN 5315-00-265-9895

Threaded Tapered Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.

