# NSN 5315-00-267-4538

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-267-4538

### Head Diameter:

Between 12.95 millimeters and 16.00 millimeters

#### Shank Diameter:

Between 9.92 millimeters and 9.96 millimeters

### **Ring Handle Diameter:**

28.580 millimeters

**Detent Quantity:** 

#### 2

**Actuation Method:** 

Push button

Grip Length:

Between 17.5 millimeters and 18.1 millimeters

#### **Actuation Type:**

Pull and push

#### **Features Provided:**

Lock open feature

# Shear Strength:

22437 double pounds per square inch

### Shoulder To Head End Distance:

51.44 millimeters

## Detent To Tapered End Distance:

Between 11.68 millimeters and 12.95 millimeters

### Material:

Stainless steel spring

### **Material Specification:**

Qq-w-423 federal specification single material response spring or ams 5673 assn standard single material response spring

#### Surface Treatment:

Passivate

### Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

### Style Designator:

Ring handle

#### Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

# A212a0

## Mil-std (military Standard):

Mil-s-5002 spec.