

View Online at <https://aerobasegroup.com/nsn/5315-00-267-6715>

First End Style:

Chamfered

Head Style:

L shape

Head Length:

2.905 inches

Tee Bolt Cylindrical Head Diameter:

0.375 inches

Under Head Length:

5.993 inches

First Step Diameter:

0.940 inches

First Step Length:

Between 1.940 inches and 2.060 inches

Second Step Diameter:

Between 0.7483 inches and 0.7490 inches

Second Step Length:

4.680 inches

Hole Arrangement Style:

Drilled through head

First Hole Diameter:

Between 0.187 inches and 0.192 inches

Distance From Centerline Of Hole To End Of Pin:

6.180 inches

First End Taper Length:

0.560 inches

Hardness Rating:

35.0 rockwell c and 39.0 rockwell c

First End Taper Angle:

20.0 degrees

First End Tip Radius:

0.060 inches

Surface Finish:

32.0 microinches large shank

Special Features:

0.187 in. Min. 0.192 in. Max. Dia. Hole perpendicular on shank end

Material:

Steel comp 3310 shoulder

Material Specification:

Mil-s-7393 military specification single material response shoulder

Style Designator:

Shoulder

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7393 spec.