## NSN 5315-00-267-6715

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-267-6715

First End Style:
Chamfered
Head Style:
L shape
Head Length:
2.905 inches
Tee Bolt Cylindrical Head Diameter:
0.375 inches
Under Head Length:
5.993 inches
First Step Diameter:
0.940 inches
First Step Length:
Between 1.940 inches and 2.060 inches
Second Step Diameter:
Between 0.7483 inches and 0.7490 inches
Second Step Length:
4.680 inches
Hole Arrangement Style:
Drilled through head
First Hole Diameter:
Between 0.187 inches and 0.192 inches
Distance From Centerline Of Hole To End Of Pin:
6.180 inches
First End Taper Length:
0.560 inches
Hardness Rating:
35.0 rockwell c and 39.0 rockwell c
First End Taper Angle:
20.0 degrees
First End Tip Radius:
0.060 inches
Surface Finish:
32.0 microinches large shank
Special Features:
0.187 in. Min. 0.192 in. Max. Dia. Hole perpendicular on shank end
Material:
Steel comp 3310 shoulder
Material Specification:
Mil-s-7393 military specification single material response shoulder
Style Designator:
Shouldor

Shoulder

## NSN 5315-00-267-6715

Headed Shoulder Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

## Mil-std (military Standard):

Mil-s-7393 spec.

